

ROOFS

FOUNDATION

VARIOUS WATERPROOFING

RESISTO

The BASIC WATERPROOFING MEMBRANE

is a 60-mil-thick, self-adhesive membrane composed of elastomeric bitumen and a trilaminate woven polyethylene. It has a nonslip surface and is very resistant to tearing and foot traffic. It has an easy-to-remove siliconetreated release sheet (split back) on the self-adhesive side.

BASIC WATERPROOFING MEMBRANE is mostly used as a base sheet in the two-ply roofing system and for any below grade waterproofing job, shower bases and wash areas.



BASIC WATERPROOFING MEMBRANE

SELF-ADHESIVE ELASTOMERIC



RESISTO

- High tensile strength
- Resistant to foot traffic
- Puncture resistant
- Anti-slip surface
- Withstands fluctuations in outdoor temperatures
- Effective and hard-wearing
- Clean and easy to install
- Requires no special tools
- UV resistant (90 days exposure)
- Flexible
- Consistent thickness

ROOFS
FOUNDATION
CONSTRUCTIONAL DETAILS

RESISTO
BASIC
WATERPROOFING MEMBRANE

UPC Code : 20" x 23' : 6 23680 65242 2
 39" x 33' : 6 23680 65241 5
 39" x 65' : 6 23680 15254 0

Product code	Dimensions	Thickness mil / mm	Approximate surface covered					
			per roll		per box		per pallet	
			ft ²	m ²	ft ²	m ²	ft ²	m ²
6524201	20" x 23' 50 cm x 7 m	60 / 1.5	37.7	3.5	75.4	7	2,714	252
65241	39" x 33' 1 m x 10 m	60 / 1.5	107.6	10	107.6	10	3,874	360
15254	39" x 65' 1 m x 20 m	60 / 1.5	215.3	19.6	215.3	19.6	5,280	490

Units per box : 20" x 23' : 2
 39" x 33' : 1
 39" x 65' : 1

Boxes per pallet : 20" x 23' : 36
 39" x 33' : 36
 39" x 65' : 25

Weight (±) per pallet : 20" x 23' : 873 lbs / 396 Kg
 39" x 33' : 1,223 lbs / 555 Kg
 39" x 65' : 1,570 lbs / 713 Kg

RECOMMENDED USES

- Roof underlayment
 - Low slope roofing (two-ply system)
- Waterproofing membrane for:
 - Concrete foundation (ICF foundation version 15244 only)
 - Shower bases
 - Bathrooms and laundry rooms (under indoor ceramic tiles* and other floor covering)
 - Deck, balcony, patio

APPLICATION TEMPERATURE

- Minimum application temperature: 50 °F (10 °C)

REQUIRED PRODUCTS



CUSTOMER SERVICE
1 877 478.8408
www.resisto.ca

* When the installation of ceramic tiles is planned, use cement glue modified with polymers. These products are sold in powder and must be mixed only with water. It is important to ensure the complete adhesion of the tiles on the membrane before the installation of the grout (minimum 48 hours). Interior application only.