

H₂O PRIMER

TECHNICAL DATA SHEET
151118RCAN2E
(supersedes -111121RCAN1E)

DESCRIPTION

H₂O PRIMER is a polymer emulsion-based primer designed to improve the adhesion of self-adhesive waterproofing membranes on most substrates. Particularly recommended when the use of solvent-based primer is not advised.

APPLICATION

The substrate must be clean, dry and free of dust, grease or other contaminant.

H₂O PRIMER may be applied with a paint brush or a roller, on concrete, wood or polystyrene surfaces as well as on gypsum plasterboard.

Average coverage: 0.1 to 0.3 L/m² (0.25 to 0.75 US gal/100 ft²).

Membranes must be installed on the same day as the application of **H₂O PRIMER**.

Minimum application temperature: -4 °C (25 °F)

The product must be at minimum 10 °C (50 °F) at the time of application.

LIMITATION

Not suitable for plastic surfaces such as vinyl siding, metal surfaces or water repellent-treated panels.

Do not use to seal self-adhesive membrane joints, as a primer between two membranes or on asphaltic boards (**RESISTOBOARD**).

PROPERTIES

Properties	H ₂ O PRIMER
Specific gravity at 20 °C (68 °F)	1,00 kg/L
Solids by weight	55 %
Colour	Blue
Viscosity	500 cP
Drying time	30 minutes to 3 hours

(All values are nominal)

PACKAGING

3.78 L and 18.9 L pails

Shelf life: Up to 18 months in original sealed containers.

KEEP FROM FREEZING.

CLEANING

Uncured material can be cleaned with water. Cured material is best removed by solvents such as mineral spirits, Varsol, Xylene, etc.

PRECAUTIONS

Keep out of reach of children. Harmful if inhaled, swallowed or when in contact with the skin. Do not pour residues in drains.

CONSULT THE MSDS PRIOR TO USE.

