



## RED ZONE ALL-WEATHER AIR BARRIER & WATERPROOFING MEMBRANE

is a self-adhesive membrane composed of elastomeric bitumen (40 mils) and a trilaminate woven polyethylene. It is an air/vapour barrier for EXTERIOR SURFACES and must be covered with sheathing or other covering materials. It has an easy-to-remove silicone-treated release sheet on the self-adhesive side.

RED-ZONE ALL-WEATHER WATERPROOFING MEMBRANE is mostly used as an air/vapour barrier for door and window frames, brick flashing, roof flashing and other construction details.



## RED ZONE ALL-WEATHER AIR BARRIER & WATERPROOFING MEMBRANE

SELF-ADHESIVE ELASTOMERIC



ALL-WEATHER 14F

- Provides a continuous air/vapour barrier
- Eliminates drafts and water leaks
- Consistent thickness
- Self-sealing around nails and screws
- UV resistant (Must be covered within 90 days)
- Can be sprayed with polyurethane foam
- Remains flexible at low temperatures
- Clean and easy to install
- Requires no special tools



## RED-ZONE ALL-WEATHER AIR BARRIER & WATERPROOFING MEMBRANE

UPC Code:	4 in × 50 ft:	6 23680 17730 7
	6 in × 50 ft:	6 23680 17731 4
	9 in × 50 ft:	6 23680 17732 1
	12 in × 50 ft:	6 23680 17733 8
	18 in × 50 ft:	6 23680 17734 5
	36 in × 50 ft:	6 23680 17727 7 (17736 9 • winter grade*)

Product code	Dimensions	Thickness mil / mm	Approximate surface covered					
			per roll		per box		per pallet	
			ft <sup>2</sup>	m <sup>2</sup>	ft <sup>2</sup>	m <sup>2</sup>	ft <sup>2</sup>	m <sup>2</sup>
17730	4 in × 50 ft 10 cm × 15 m	40 / 1.0	16.7	1.5	150	13.86	5400	499
17731	6 in × 50 ft 15 cm × 15 m	40 / 1.0	25	2.3	150	13.86	5400	499
17732	9 in × 50 ft 23 cm × 15 m	40 / 1.0	37.5	3.4	150	13.86	5400	499
17733	12 in × 50 ft 30 cm × 15 m	40 / 1.0	50	4.6	150	13.86	5400	499
17734	18 in × 50 ft 46 cm × 15 m	40 / 1.0	75	6.9	150	13.86	5400	499
17727 *17736	36 in × 50 ft 92 cm × 15 m	40 / 1.0	150	13.86	150	13.86	5400	499

Units per box:	4 in × 50 ft:	9
	6 in × 50 ft:	6
	9 in × 50 ft:	4
	12 in × 50 ft:	3
	18 in × 50 ft:	2
	36 in × 50 ft:	1

Boxes per pallet:	36
Weight (±) per pallet:	1,000 lbs / 454 Kg

### RECOMMENDED USES

- Exterior surfaces (except below grade)
- Door and window frames
- Solarium structures, skylights, etc.
- Brick flashing, roof flashing and other building details
- Lap joints (between strips of RESISTO waterproofing membranes installed without overlaps).

### APPLICATION TEMPERATURE

- Minimum application temperature:  
14°F (-10°C)

### REQUIRED PRODUCT



OR



PRINTED IN CANADA • AR372-01/2012



CUSTOMER SERVICE

1 877 478.8408

www.resisto.ca  
www.resisto.us