

REDZONE PRO is a self-adhesive through-wall membrane designed for light commercial buildings. It ensures air and water vapor waterproofing. REDZONE PRO is composed of SBS modified bitumen and a tri-laminated woven polyethylene facer. The tri-laminated woven polyethylene is compatible with the use of sprayed polyurethane foam insulation.

REDZONE PRO is also used as masonry flashing, transition membrane and waterproofing membrane around openings.

Bar Codes

• 14005	91 cm x 22,9 m	6 23680 14005 9
• 1730002	45 cm x 22,9 m	6 23680 00054 4
• 1730003	30 cm x 22,9 m	6 23680 00055 1
• 1730004	23 cm x 22,9 m	6 23680 00056 8
• 1730006	15 cm x 22,9 m	6 23680 00057 5
• 1730009	10 cm x 22,9 m	6 23680 00058 2

General Information

Thick	ness	Weight	Surface	Underface	Minimum installation temperature	Service temperature
40 mil (1	1,0 mm)	0,2 lb/ft² (1 kg/m²)	Tri-laminated woven polyethylene	Silicone release film	14 °F (-10 °C)	-49 to 194 °F (-45 to 90 °C)

Conditioning

REDZONE PRO

Dimensions	Bar Codes	Units per box	Boxes per pallet	Units per pallet
3 ft x 75 ft (91 cm x 22,9 m)	6 23680 14005 9	1	36	36

REDZONE PRO in cut rolls

Dimensions	Bar Codes	Units per box	Boxes per pallet	Units per pallet
18 in x 75 ft (45 cm x 22.9 m)	6 23680 00054 4	2	24	48
12 in x 75 ft (30 cm x 22.9 m)	6 23680 00055 1	3	24	72
9 in x 75 ft (23 cm x 22,9 m)	6 23680 00056 8	4	24	96
6 in x 75 ft (15 cm x 22.9 m)	6 23680 00057 5	6	24	144
4 in x 75 ft (10 cm x 22.9 m)	6 23680 00058 2	9	24	216

Required products

Prepares and evens the surface to improve adhesion of REDZONE PRO



or





or

EXTERIOR PRIMER

H₂O PRIMER

LOW V.O.C. PRIMER

Complementary product

ELASTOMERIC SEALER:

Caulking mastic for filling of joints and cracks



